

# AESEBU-DSTB

AUDIO DISTRIBUTOR SYSTEM

MODEL AESEBU-DSTB-23



## ORDERING INFORMATION

Model	Description
<b>AESEBU-DSTB-23</b>	The digital audio distributor systems allows you to split the audio signal in input and redistribute it on multiple outputs. 2 x IN > 3 OU



**AESEBU-DSTB-23**

Audio Distributor System.

## FEATURES

**PRIMARY APPLICATION:** the digital audio distributor systems allows you to split the audio signal in input and redistribute it on multiple outputs.

**TECHNICAL FEATURES:** one digital signal is distributed actively on 4-way for AESEBU-DSTB-14 model or on 7-way for AESEBU-DSTB-17 model. On AESEBU-DSTB-14 model the two digital signals in input are distributed actively on 3-way; whereas on AESEBU-DSTB-14 model the three digital signals in input are distributed actively on 2-way.

**HARDWARE FEATURES:** the audio distribution system housed in lightweight and rugged stainless steel rack cases having the dimension of 1 HE.

## AESEBU-DSTB-23

Parameters		Value	Notes
<b>GENERALS</b>			
Operating temperature		From -10 °C to +50 °C	
Operating humidity	%	95	Without condensing
<b>POWER REQUIREMENTS</b>			
AC Power input	AC Supply Voltage	VAC	80 ÷ 260
	Active Power Consumption	W	2
	Connector		VDE IEC Standard
<b>MECHANICAL DIMENSIONS</b>			
Physical dimensions	L x H x W	mm / inch	483 / 19
		mm / inch	44 / 3 1/2
Weight		kg	About 2
<b>AUDIO INPUTS</b>			
AES/EBU	Connector		2x XLR
	Impedance	Ohm	110
<b>OUTPUTS</b>			
AES/EBU	Connector		3x XLR
	Impedance	Ohm	110
<b>FUSES</b>			
On mains			External fuse F T 1A - 5X20 mm
On services			X
On PA supply			X
On driver supply			X

All pictures are RVR's property and they are only indicative and not binding. The pictures can be modified without notice. These are general specifications. They show typical values and are subject to change without notice.



**R.V.R. Elettronica S.r.l.**

Via del Fonditore 2/2 c  
40138 Bologna - Italy  
Phone +39 051 6010506  
info@rvr.it

**www.rvr.it**