

AESEBU-DSTB

AUDIO DISTRIBUTOR SYSTEM

MODEL AESEBU-DSTB-32



ORDERING INFORMATION

Model	Description
AESEBU-DSTB-32	The digital audio distributor systems allows you to split the audio signal in input and redistribute it on multiple outputs. 3 x IN > 2 OUTs.



AESEBU-DSTB-32

Audio Distributor System.

FEATURES

PRIMARY APPLICATION: the digital audio distributor systems allows you to split the audio signal in input and redistribute it on multiple outputs.

TECHNICAL FEATURES: one digital signal is distributed actively on 4-way for AESEBU-DSTB-14 model or on 7-way for AESEBU-DSTB-17 model. On AESEBU-DSTB-14 model the two digital signals in input are distributed actively on 3-way; whereas on AESEBU-DSTB-14 model the three digital signals in input are distributed actively on 2-way.

HARDWARE FEATURES: the audio distribution system housed in lightweight and rugged stainless steel rack cases having the dimension of 1 HE.

AESEBU-DSTB-32

Parameters		Value	Notes	
GENERALS				
Operating temperature		From -10 °C to +50 °C		
Operating humidity	%	95	Without condensing	
POWER REQUIREMENTS				
AC Power input	AC Supply Voltage	VAC	80 ÷ 260	Full Range
	Active Power Consumption	W	2	
	Connector		VDE IEC Standard	
MECHANICAL DIMENSIONS				
Physical dimensions	L x H x W	mm / inch	483 / 19	EIA rack
		mm / inch	44 / 3 1/2	1HE
Weight		kg	About 2	
AUDIO INPUTS				
AES/EBU	Connector		3x XLR	Balanced (female)
	Impedance	Ohm	110	
OUTPUTS				
AES/EBU	Connector		2x XLR	Balanced (female)
	Impedance	Ohm	110	
FUSES				
On mains			External fuse F T 1A - 5X20 mm	
On services			X	
On PA supply			X	
On driver supply			X	

All pictures are RVR's property and they are only indicative and not binding. The pictures can be modified without notice. These are general specifications. They show typical values and are subject to change without notice.



R.V.R. Elettronica S.r.l.
Via del Fonditore 2/2 c
40138 Bologna - Italy
Phone +39 051 6010506
info@rvr.it

www.rvr.it