

Solid State Amplifiers

> modular **PJM-C series**

PJ5000U-K



PJ5000U-K front view

Features

- > **PRIMARY APPLICATION:** uncompromised high amplification power. Ideal to supplement mid to high power stations.
- > **AMPLIFIER FEATURES:** exceptional-gain amplifier with very low input drive power requirement and adjustable power output from 10 to 100 %. Available (optionally) **LD "Low Drive"** technology which reduces required input drive power to as little as 5W.
- > **HARDWARE FEATURES:** easy handling, ultra-compact and indeformable thanks to the stainless steel chassis, in 4 rack units.
- > **RELIABILITY/CONTINUITY:** APC (Automatic Power Control), Foldback protection, redundancy of amplification units and redundancy of power supply units to mantene always on the broadcast transmission, ensure reliable operation under any operating conditions.
- > **OPERATING EFFICIENCY:** incorporate a PFC (Power Factor Corrector) power supply, that provides the utmost efficiency for enhanced energy saving and environmental protection, which added to LD-MOSFET technology ensure high efficiency, better than 70% across the bandwidth.
- > **USER-FRIENDLY FEATURES:** configurable both in single and three phase. Five pushbuttons for user/device interaction and software that offers a simple, intuitive interface.
- > **INTERFACE CONTROL:** total control thanks to microprocessor easily programmed from menu with all key parameters displayed on LCD.
- > **EASE OF MAINTENANCE:** advanced module engineering ensures extreme ease of access and simple maintenance.
- > **REMOTE CONTROL:** supplied with telemetry connectors and is compatible with all **RVR** telemetry systems and other popular transmitter remote control systems.
- > **REGULATORY COMPLIANCE:** state-of-the-art technology and design results in equipment that is in full compliance with FCC, CCIR, and EC standards.

Caratteristiche

- > **PRIMARY APPLICATION:** estrema potenza di amplificazione senza compromessi. Ideale come complemento per stazioni di media-alta potenza.
- > **AMPLIFIER FEATURES:** amplificatore ad alto guadagno con potenza di pilotaggio in ingresso estremamente basso e potenza di uscita regolabile dal 10 al 100%. Disponibile anche con **LD (Low Drive)** che abbate la potenza di pilotaggio richiesta a soli 5 W (versione vendibile opzionalmente).
- > **HARDWARE FEATURES:** maneggevole, estremamente compatto e indeformabile perché realizzato in chassis di acciaio inox, in sole 4 unità rack.
- > **RELIABILITY/CONTINUITY:** elevata continuità di esercizio in qualsiasi condizione di lavoro, assicurato dal controllo automatico APC, protezione di Foldback, ridondanza del gruppo di amplificazione e del gruppo alimentazione che mantiene sempre in onda la trasmissione.
- > **OPERATING EFFICIENCY:** per un risparmio di risorse energetiche e ambientali, utilizza un alimentatore PFC (Power Factor Corrector) che sommato alla tecnologia LD-MOSFET garantisce rendimenti elevati, superiori al 70% su tutta la banda.
- > **USER-FRIENDLY FEATURES:** configurabile sia in monofase che trifase. Cinque tasti a pressione per l'interazione fra l'utente e l'apparato unita ad un software intuitivo e semplificato.
- > **INTERFACE CONTROL:** controllo completo basato su microprocessore e da menu con lettura su display LCD di tutti i parametri principali.
- > **EASE OF MAINTENANCE:** estrema accessibilità e semplicità di manutenzione grazie ad una avanzata ingegnerizzazione modulare dell'apparato.
- > **REMOTE CONTROL:** presenza di connettori per la telemetria ed il telecontrollo compatibile con tutti i sistemi di telemetria della **RVR Elettronica**.
- > **REGULATORY COMPLIANCE:** tecnologia moderna e pienamente rispondente alle normative EC, FCC ed CCIR.

Solid State Amplifiers

BROADCAST
EQUIPMENT

(Oirt, JPN &
China Band
others
on request)

Technical specifications

Parameter		PJ5000U-K	Value
GENERALS			
Frequency range			FCC - CCIR - OIRT - JPN - CHN
Rated output power			5000 W
Driver power for rated output			70 W
Max input power before protection			100 W
Environmental working conditions			-10 °C to + 50 °C / 95% relative Humidity non condensing
POWER REQUIREMENTS			
AC Power Input	AC Supply Voltage		240 VAC ±15% monophasic ; 400 VAC ±15% threephase
	Active Power Consumption		8000 W
	Overall Efficiency		Typical < 70 %
	Connector		ILME CQ 4/2
MECHANICAL DIMENSIONS			
Physical Dimensions	L x H x W		483 mm x 178 mm x 695 mm
Weight			about 45 kg
Cooling			Forced, with internal fan
Acoustic Noise			< 78 dBA
INPUTS			
RF Input			50 Ohm (N type)
OUTPUTS			
RF Output			50 Ohm (7/8" EIA flange type)
RF Monitor			50 Ohm (BNC) approx. -60 dBc
FUSES			
On Mains			3 External fuses F20T 10x38
On P.A. Supply			8 Internal fuses F 25 A

All pictures are RVR's property and they are only indicative and not binding. The pictures can be modified without notice.
These are general specifications. They show typical values and are subject to change without notice.

CE 99/5/CE Revision: 04/17

Ordering Information

Code - Codice	Description - Descrizione
Options for PJM-C – Opzioni per PJM-C	
/LD-PJM-C	Low drive power (less than 5W). Bassa potenza di pilotaggio (meno di 5").