PJ-K-KLC SERIES



PJ-K-KLC

MODEL PJ25K-KLC



ORDERING INFORMATION		
Model	Description	
PJ25K-KLC	25.000W Liquid cooled system.	



1

R.V.R. Elettronica S.r.l. Via del Fonditore, 2/2c 40138 Bologna Italy Phone +39 0516010506 Fax +39 0516011104 sales@rvr.it - www.rvr.it



PJ-K-KLC SERIES



PJ25K-KLC

25.000W Liquid cooled system.

FEATURES

POWER & QUALITY: With the family of RVR's liquid transmitters based on the U-KLC series, is possible to realize compact equipments up to 20kW, with high energy savings thanks to the use of high efficiency pumps and no forcing ventilation. The Cooling system is with low pressure circuit and double pump in automatic switching and diagnostics.

USER-FRIENDLY FEATURES: user-friendly software and a simple, intuitive HM interface let you easily set up and control all machine operating parameters. user-friendly software and a simple, intuitive HM interface let you easily set up and control all machine operating parameters.



R.V.R. Elettronica S.r.l. Via del Fonditore, 2/2c 40138 Bologna Italy Phone +39 0516010506 Fax +39 0516011104 sales@rvr.it - www.rvr.it



PJ25K-KLC					
Parameters	U.M.	Value	Notes		
GENERALS					
RF Output power	kW	25			
Frequency range		87.5 – 108 MHz programmable in 1,10 or 1000 KHz steps			
Frequency stability	ppm	±1			
Class of emission		180KF8E			
Stereo transmission		Acc. To ITU-R / Rec. 450 (Pilot tone)			
RF output impedance		50 Ω, Unbalanced			
RF Output connector		3-1/8" EIA Flange			
VSWR		1.41:1 with automatic fold-back at higher VSWR			
Asynchronous AM S/N Ratio		≥ 70 dB unweight, referred to 100% AM modulation at 400 Hz Pre-emphasis and without FM modulation			
Synchronous AM S/N Ratio		≥ 55 dB, reference to 100% AM modulation at 400 Hz, 50 μs Pre-emphasis with the second	th FM modulation at 75 KHz of deviation		
Harmonics suppression and Spurious	dB	Typically 85			
Overall efficiency	%	Typically 70/72			
RF Harmonics		Exceeds ETSI/CCIR/FCC requirements			
RF Spurious		Exceeds ETSI/CCIR/FCC requirements			

All pictures are RVR's property and they are only indicative and not binding. The pictures can be modified without notice. These are general specifications. They show typical values and are subject to change without notice.



3

R.V.R. Elettronica S.r.l. Via del Fonditore, 2/2c 40138 Bologna Italy Phone +39 0516010506 Fax +39 0516011104 sales@rvr.it - www.rvr.it







R.V.R. Elettronica S.r.l. Via del Fonditore 2/2 c 40138 Bologna - Italy Phone +39 051 6010506 info@rvr.it

www.rvr.it